

## CLAIMS

What is claimed is:

5

Sub 112

1. A hose assembly comprising:

a tubular first layer, comprising a polymeric material resistant to chemical and heat degradation;

112 NA a jacket disposed about said inner layer;

10 at least one Aramid-like braided layer disposed between said inner and  
NA outer layers.

2. The hose assembly according to claim 1, further characterized by said braided layer comprising Aramid fibers.

15

3. The hose assembly according to claim 2, wherein said braided layer further includes glass fibers commingled with said Aramid fibers.

4. The hose assembly according to claim 2, wherein said polymeric  
20 material of said tubular first layer is a polyketone.

112 112 5. The hose assembly according to claim 2, wherein said polymeric material of said first layer is a polymeric fluorocarbon.

112 112 6. The hose assembly according to claim 2, wherein said polymeric material of said jacket is a polymeric material.

7. The hose assembly according to claim 6, wherein said polymeric material of said jacket is a polymeric fluorocarbon or a polyamide.

10 8. The hose assembly according to claim 6, wherein said polyamide material of said jacket is unexpanded.

112  
Jacket  
can fluoro  
be fluoro

15 9. The hose assembly according to claim 8, wherein said polyamide material of said jacket is selected from the group consisting essentially of: nylon 6; nylon 6,6; nylon 11; and nylon 12.

10. The hose assembly according to claim 5, wherein said polymeric fluorocarbon material of said first layer is expanded.

20 11. The hose assembly according to claim 10, wherein said polymeric fluorocarbon material of said first layer is selected from the group consisting

essentially of: polytetrafluoroethylene; perfluorinated ethylene-propylene; perfluoralkoxy fluorocarbon resin; and polyfluoroethylene.

12. The hose assembly according to claim 1, wherein said first layer  
5 further includes a conductive means in said first layer for conducting electrical charges along the length of the first layer.

13. The hose assembly according to claim 1, wherein said hose  
assembly further includes a conductive layer containing therein conductive  
10 means for conducting electrical charges along the length of said hose assembly.

14. The hose assembly according to claim 12 or 13, wherein said  
conductive means is carbon black.

15. The hose assembly according to claim 1, wherein said hose  
assembly further includes a coupling means adapted to engage the ends of said  
hose assembly for interconnecting said hose assembly to a flow of fluid.

16. A method of making a hose assembly by:  
20 forming a tubular first layer;  
disposing an Aramid-like braid about the first layer; and  
extruding a jacket over the braid.

17. The method according to claim 12, wherein said forming step further includes extruding the tubular first layer.

5  
Sub  
A2

18. A method of making a hose assembly by:  
forming a tubular first layer;  
dipping the tubular first layer in an adhesive emulsion; and  
disposing an Aramid-like braid about the adhesive coated first  
layer.

10

Add  
C3